

SIA RĪGAS DĪZELIS DG OEM make PORTABLE DIESEL ELECTRIC GENERATOR for defence application

Model: 1EA2-5KhM-N



Technical specification 1EA2-5KhM-N

TECHNICAL SPECIFICATION FOR DC 2-5 kW PORTABLE DIESEL ELECTRIC GENERATOR

Generating set model	1EA2KhM-N	1EA5KhM-N	
Manufacturer	SIA "RĪGAS	SIA "RĪGAS DĪZELIS DG"	
Execution	Open frame with soundproof panels		
Operation temperatures:	-20 °C + 40 °C		
Current characteristics	DC, single-phase		
Rated voltage, V	28		
Rated current, A	60-70	185-200	
Rated Power, kW	Approx. 1,9	Approx. 5,0	
Hourly fuel consumption at rated power, I/h	1,1	2,5	
Oil consumption per hour at rated power, I/h	0,0021	0,006	
Dimensions, mm	650x437x465(H)	650 x 450 x 520(H)	
Weight dry, kg	74	110	
Diesel Engine	15LD225,	KD 15-500	
	Lombardini / Kohler	Kohler	
Number of cylinders		1	
Crankshaft speed, rpm	3600		
Cooling system	air		
Starting system	ma	manual	
Fuel tank capacity, 1	10	10	
Oil sump capacity, 1	0.9	1,5	
Fuel	According to EN590		
Alternator DC	80 A	260 A	
Protection class	IP54		
Control panel	Ammeter, Voltmeter, Power switch, Engine hour viewer, Socket, Empty socket		
Protection	IP65		
Noise level	(75÷85) dBA at 7 m		
Color	RAL 6003, 6031 or other Customer' selected		
Set of standard tools for maintenance	+		

Documentation	
Operational manual for complete generating set + (in Customer's and/or English languages)	
Spare parts catalogs	+ (in English language)
Package of design documentation (drawings, diagrams, etc.)	+ (in English language)
Factory test report	+
Warranty	24 months from delivery
	(but not more than 1000 operating hours)

Options	
1	Cover for a product made of special fabric
2	Special cable for genset connection with Customer's connection box
3	Set of filters for maintenance for 500 or 1000 operating hours
4	Exhaust piping system under Customer's request



Address: 36 Ganibu dambis, Riga, Latvia, LV-1005 Telephone: +371 67391781, +371 67381626

Fax: +371 67381925
E-mail: sales@rigasdizelis.lv
Website: www.rigasdizelis.lv